

EURO COACH

Specifications

Frame Construction

Euro Coach V33/V29 Box section steel construction hot dipped at 500°C with five year warranty against corrosion with an extension option of five years. Compliant with R66 roll over requirements.

Chassis Frame

CANNON VARIANT Chassis Cowl Softline 6mm steel channel ladder type bolted construction, electronic vehicle stability control (VSC), Electronic Braking Systems (EBS), Cruise Control (CC).

Engine

Cummins 135 KW 180hp at 700NM torque.

Cummins 157 KW 210hp at 760NM torque.

Euro 5/6.

Transmission

ZF 5-speed manual, 6 speed manual, 6 speed AS Tronic ZF.

Suspension

Front: Parabolic leaf suspension with double acting shock absorbers and stabilisers.

Rear: ECAS. 2 air bellow spring with steel leaf, double acting shock absorbers and stabilisers.

Electric Height Control (EHC).

Brakes

Full Air Disc brakes on front and rear axles with ASR (Anti Slip Control), ABS.

Exhaust brake & Telma magnetic retarder.

Fuel Tank

Fuel capacity 185 litres. Ad blue 25 litres.

Luggage Compartments

Interior hand luggage racks, large boot, 3 side lockers up to 5 cubic metres of space.

Saloon Heating System

Air conditioning system by Eberspacher. Twin saloon convector heating.

Glazing

Passenger panoramic dark tint privacy double glazing.

Body Dimensions

L: 8740mm x W: 2350mm x H: 3100mm

WB: 4815, Rear OH: 2870mm, Front OH: 1055mm

